



02 GLARELESS DOWN LIGHT ADJUSTABLE

SPECIFICATIONS

Power consumption 8.7W

Weight 0.21kg

Body Materials Die-cast aluminum
Powder coating painted

Lens Materials Polycarbonate


CRI Ra ≥ 80
Ra ≥ 90
Ra ≥ 97

Kelvin 2700 ■
3000 ■
3500 ■
4000 ■

DIMMER 0-10V	POWER UNIT OUTSIDE	TIA 30°	Ra/A 355	CUT OUT 60	GLARE CUT 35
CRI Ra ≥ 80	CRI Ra ≥ 90	CRI Ra ≥ 97	PROTECTION MODE IP20	LIFE TIME 40000h	




DRAWING





02 GLARELESS DOWN LIGHT ADJUSTABLE

OPTICAL DATA Ra ≥ 90



POWER SUPPLY / DIMMER SWITCH



Suitable Power supply for NonDimmable
ECIV020111B

Suitable Power supply for 0-10V Dimmable
ECIV020111B-D



Recommended Dimmer Switch
WTD5 57626

OPTIONAL ACCESSORIES



Edge smoothing Lens
ES-45



Diffusion Lens
DL-45/1.5



Diffusion Lens
DL-45/3.0



Diffusion Lens
DL-45/4.5



Spread Lens
SL-45



Honeycomb Louver
HL-45