



02 GLARELESS DOWN LIGHT ADJUSTABLE

SPECIFICATIONS

Power consumption 8.8W / 9.3W

Weight 0.3kg

Body Materials Die-cast aluminum
Powder coating painted

Lens Materials Polycarbonate


CRI Ra \geq 80
Ra \geq 90
Ra \geq 97

Kelvin 2700 ■
3000 ■
3500 ■
4000 ■

DIMMER 0-10V	POWER UNIT OUTSIDE	TIA 30°	Ra/A 355	CUT OUT 75	GLARE CUT 35
CRI Ra \geq 80	CRI Ra \geq 90	CRI Ra \geq 97	PROTECTION MODE IP20	LIFE TIME 40000h	



DRAWING






02 GLARELESS DOWN LIGHT ADJUSTABLE


OPTICAL DATA $Ra \geq 90$




UDL-S75NAGL-27




UDL-S75NAGL-30




UDL-S75NAGL-35




UDL-S75NAGL-40




UDL-S75MAGL-27




UDL-S75MAGL-30




UDL-S75MAGL-35




UDL-S75MAGL-40




UDL-S75WAGL-27




UDL-S75WAGL-30



UDL-S75WAGL-35



UDL-S75WAGL-40




POWER SUPPLY / DIMMER SWITCH



Suitable Power supply for NonDimmable
ECIV02511JIS



Suitable Power supply for 0-10V Dimmable
ECIV02511JJP-D



Recommended Dimmer Switch
WTFD 57626

OPTIONAL ACCESSORIES



Edge smoothing Lens
ES-54



Diffusion Lens
DL-54/1.5



Diffusion Lens
DL-54/3.0



Diffusion Lens
DL-54/4.5



Spread Lens
SL-54



Honeycomb Louver
HL-54