




# 02 GLARELESS DOWN LIGHT FIXED

## SPECIFICATIONS

<b>Power consumption</b>	14.3W / 15.4W
<b>Weight</b>	0.28kg
<b>Body Materials</b>	Die-cast aluminum Aluminum extrusion Powder coating painted
<b>Lens Materials</b>	Polycarbonate
<b>CRI</b>	Ra ≥ 80 Ra ≥ 90 Ra ≥ 97
<b>Kelvin</b>	2700 <span style="color: orange;">■</span> 3000 <span style="color: yellow;">■</span> 3500 <span style="color: gray;">■</span> 4000 <span style="color: blue;">■</span>




## DRAWING






# 02 GLARELESS DOWN LIGHT FIXED

## OPTICAL DATA $Ra \geq 90$




Narrow


**UDL-M75NFGL-27**




**UDL-M75NFGL-30**



**UDL-M75NFGL-35**




**UDL-M75NFGL-40**




Medium


**UDL-M75MFGL-27**





**UDL-M75MFGL-30**



**UDL-M75MFGL-35**




**UDL-M75MFGL-40**




Wide


**UDL-M75WFGL-27**




**UDL-M75WFGL-30**



**UDL-M75WFGL-35**



**UDL-M75WFGL-40**



## POWER SUPPLY / DIMMER SWITCH



Suitable Power supply for NonDimmable  
ECIV03211JS



Suitable Power supply for 0-10V Dimmable  
ECIV03211JP-D



Recommended Dimmer Switch  
WTD5 57626

## OPTIONAL ACCESSORIES



Edge smoothing Lens  
ES-54



Diffusion Lens  
DL-54/1.5



Diffusion Lens  
DL-54/3.0



Diffusion Lens  
DL-54/4.5



Spread Lens  
SL-54



Honeycomb Louver  
HL-54