



# 02 GLARELESS DOWN LIGHT FIXED

## SPECIFICATIONS

**Power consumption** 8.8W / 9.3W

**Weight** 0.28kg

**Body Materials** Die-cast aluminum  
Aluminum extrusion  
Powder coating painted

**Lens Materials** Polycarbonate

**CRI** Ra ≥ 80  
Ra ≥ 90  
Ra ≥ 97

**Kelvin** 2700 ■  
3000 ■  
3500 ■  
4000 ■



Black Chrome with White trim



Chrome with Black trim



White Paint finish with White trim




Black Chrome with Black trim



Black Paint finish with Black trim

VOLTAGE 100-240	LED SYS COB	DIMMER 0-10V	POWER UNIT OUTSIDE	CUT OUT 75	GLARE CUT 35
CRI Ra ≥ 80	CRI Ra ≥ 90	CRI Ra ≥ 97	PROTECTION MODE IP20	LIFE TIME 40000h	

## DRAWING






# 02 GLARELESS DOWN LIGHT FIXED


## OPTICAL DATA Ra ≥ 90




UDL-S75NFGL-27




UDL-S75NFGL-30




UDL-S75NFGL-35




UDL-S75NFGL-40




UDL-S75MFGL-27




UDL-S75MFGL-30




UDL-S75MFGL-35




UDL-S75MFGL-40




UDL-S75WFGL-27




UDL-S75WFGL-30



UDL-S75WFGL-35



UDL-S75WFGL-40



## POWER SUPPLY / DIMMER SWITCH



Suitable Power supply for NonDimmable  
ECIV02511JIS



Suitable Power supply for 0-10V Dimmable  
ECIV02511JJP-D



Recommended Dimmer Switch  
WTDF 57626

## OPTIONAL ACCESSORIES



Edge smoothing Lens  
ES-54



Diffusion Lens  
DL-54/1.5



Diffusion Lens  
DL-54/3.0



Diffusion Lens  
DL-54/4.5



Spread Lens  
SL-54



Honeycomb Louver  
HL-54